ABOUT WIFI

WI-FI CONNECTION

Before using your Wi-Fi thermostat for the first time, you must configure the Wi-Fi signal and settings through your smartphone or tablet ,This will allow communication between your connecteddevices

Step 1 Download your APP (Fig1-1)







Fig 1-1

Fig 1-3 Android

Search for "Smartlife" in Apple Store or Google Play or use a browser to scan the QR code above (Figure 1-2), and complete account registration and installation according to the guidance of the APP.

Fig 1-2 IOS

Step 2. Connect the thermostat Check the tutorial below to complete the connection

and setup. Method 1: Scan the QR code to configure the network guide

(Fig 2.1-Fig 2.3)



I I	•		
H H			110
	1000	1-0	H
1 1	U	1	
	Fig	g2.3.1	

Method 2: Ordinary distribution

network guidance

(Fig. 2. 1&Fig. 2.3.1)



Q 81.57 .

Network distribution mode:

When the thermostat is off, press

thermostat screen flashes quickly

and then operate according to the

E2 Mode In

and hold the " 𝗡 "until the

and displays the " 🛜 " icon,

following figure (Fig 2.4-Fig 2.7).

Reset the device first.

Power at the device and confirm shatt indicators highly balance binder

Assailing Devestion

Confirm indicator regidly blick

Fig2.4

1、EZ Mode

Earlorit



Sear-

Done Added successfully themostal7 / Deskar initial spationists

2、AP Mode

When the thermostat is off, press and hold the " \forall " until the thermostat screen flashes slowly and the " 🖗 " icon is displayed (if the " 奈 " icon appears, continue to press the " 🏹 " until the thermostat screen Flashes slowly and displays the " 🙋 " icon), and then operate according to the following figure (Fig 2.8-Fig 2.14).



Fig2.8



AP Mode
fierat.
1
)
-



- Smarti, Au 10008

- 51,4888





Manual

Room temp.

Fig2.5

Fig2.3

Fig2.7

Fig2.10

Fig2.11

< WLAN



SmartLife 11A3

return to the "smartlife" APP



More settings

1736 D <	104730	
() thermostat 7	· <u> </u>	Modify the name of the thermostat
Device Information	5	View the virtual ID of the thermostat
Tap-to-Run and Automat	ion 3	
The desire (Second)		
Ness Coogle Associate	Searthage 64000	Connect smart voice audio guide
Dening (Main Restfundant)		
Offline Notification	CD	
1994 F		Share the thermosta
Share Device	1.5	with your family
Create Group	1.6	Group multiple thermostats for
FAQ & Feedback	1	management
Add to home screen	15	
Check Device Network	Check Now 2	
Device Update	No apteirs waitetie >	
Renzve	Device	



APP operation interface description (heating thermostat))



SIMPLE EXCEPTION HANDLING

No.	Phenomenons	Handling
1	Power is on but without display.	* Check if the terminals between LCD panel and Power Unit Box is loosen.
2	Without output but display works.	* Use a new LCD panel or new Power Unit Box to replace the old one.
3	Room Temp. Is a little different from the actual.	$\ensuremath{^*}$ Do temperature calibration in item 1 of high senior options

SERVICE

Your thermostat carries an 24 months warranty from date of purchase. Service outwith the warranty period may incur a charge. More detail please contact with us directly.